



FOOT OPERATED SEALING MACHINES

| Adjustable electronic timer | Tilttable sealing jaw | Adjustable bag rest | Ease of operation | High productivity | Visual indication during sealing | Audio indication at the end of sealing | Hot bar sealer with energy regulator for sealing laminated pouches

Technical specifications

Model	Seal (mm)		Power		Dimension (mm)			Weight (Kg)
	Length	Width	V	VA	L	B	H	
Impulse Sealers								
SH 450 FEP	450	1.6/3x2/5	240	750	545	510	950	26.5
QS 200 F	200	1.6	240	245	660	620	1050	17
QS 200 FE	200	5	240	470	660	620	1050	18
QS 200 FP	200	3x2	240	750	660	620	1050	22
QS 300 F	300	1.6	240	400	660	620	1050	19
QS 300 FE	300	5	240	600	660	620	1050	22
QS 300 FP	300	3x2	240	800	660	620	1050	24
QS 400 F	400	1.6	240	470	660	620	1050	20
QS 400 FE	400	5	240	720	660	620	1050	23
QS 500 F	500	1.6	240	560	660	620	1050	20
QS 500 FE	500	5	240	750	660	620	1050	23
QS 600 F	600	1.6	240	650	700	620	1050	23
QS 600 FE	600	5	240	920	700	620	1050	26
QS 900 F	900	1.6	240	950	1000	620	1050	30
QS 900 FE	900	5	240	1200	1000	620	1050	35
Model	Seal (mm)		Power		Dimension (mm)			Weight
	Length	Width	V	VA	L	B	H	
Hot bar Sealers								
200 FHM	200	14.5	240	340	660	620	1050	
300 FHM	300	14.5	240	500	660	620	1050	
400 FHM	400	14.5	240	650	660	620	1050	