



IS 130C



IS 50C/120C



IS 80P/IS 120P

## INDUCTION SEALERS

Induction sealers are used for hermetically sealing the plastic & glass bottle caps with aluminum foils. This makes the bottles leak-proof & tamper evident and offers extended shelf life. Induction sealers are widely used in Pharmaceutical, Chemical, Lubricant, Cosmetic and Food industries.

### TECHNICAL SPECIFICATIONS

	IS 130C	IS 50C	IS 120C
Power	2 KW@ 240 V 50Hz	1.5 KW@ 240 V 50Hz	2 KW@ 240 V 50Hz
Conveyor speed	0~ 12 Mts./Min.	0~ 10 Mts./Min.	0~ 10 Mts./Min.
Bottle Dia	50 ~ 130 mm	20 ~ 50 mm	30 ~ 120 mm
Bottle Height	40 ~ 300 mm	40 ~ 200 mm	40 ~ 400 mm
Dimensions (mm)	1550 x 580 x 1430	1170 x 490 x 640	1170 X 610 X 655
Weight	72 Kg	38 Kg	40 Kg
Sealing Speed	up to 20 bottles/min	up to 20 bottles/min	up to 20 bottles/min

\*Sealing speed depending on bottle size

### PORTABLE

Parameter	IS 80P	IS 120P
Supply	240VAC / 50Hz	240VAC / 50Hz
Power Consumption	500W	1000W
Dimension (mm)	345 x 330 x 145	345 x 330 x 145
Weight	3.5Kg	3.6Kg
Sealing Head Dimension (mm)	115 x 190	158 x 190
Bottle Dia (mm)	20 to 80	40 to 120